



PN# 11000013025
 Hook 30mm (1")
 PN# 11000013026
 Loop 30mm (1")

**Shieldex® Conductive
 30mm (1") Hook & Loop**



- Purpose: Electrically conductive fastener system, produces a closure with very little gap impedance
- Description: Woven nylon base Hook & Loop entirely coated in Silver (Ag)
- Surface Resistivity: Hook or Loop < 1.4 Ohms / sq inch
- Closure Resistance: < 0.8 Ohms through resistance
- Cycle Life: 7,000 opening and closing
- Temperature Range: -40°C to 90°C / -40°F to 212°F
- Attachment: Sew, glue, or ultrasonic bond
- Packaging: Standard 25 Lm / 27.5 Lyd spool (custom cut lengths available)



PRODUCT APPLICATION

- ⇒ EMI/RFI Shielding
- ⇒ Ground straps & ESD applications
- ⇒ Clothing for E-smog
- ⇒ RF tents and other shielding shelters
- ⇒ RF tight pouches and bags
- ⇒ RF ground planes and covers
- ⇒ Electrical sensors and attachments for medical use

Accreditations:
 RoHS: Compliant
 Reach: Compliant
 Acc. ISO 9001:2000

V Technical Textiles, Inc
 4502 State Rt. 31
 Palmyra, NY 14522
 Phone: 315-597-1674
 Fax: 315-597-6687
 Web: www.vtechtextiles.com
 Email: whoge@rochester.twcbc.com



Statex Productions & Vertriebs GmbH
 Kleiner Ort 11 28357
 Bremen Germany
 Tel: +49 421 275047/8,
 Fax: +49 421 273643
 info@statex.de

