



PN# 600500105



Shieldex® 2611

- Purpose: Conductive knitted net for general use
- Description: Silver (Ag) plated knitted nylon net
- Plating: 99% pure silver
- Holes per cm: Length 12; Width 10 (hexagonal mesh)
- Surface Resistivity: Average < 1.0 Ohms / □
- RF Shielding Effectiveness: Average > 35 dB from 30Mhz to 10Ghz
- Temperature Range: -40°C to 100°C / -40°F to 212°F
- Total Thickness: 0.009" (0.22mm) ± 10%
- Abrasion Resistance: 10,000 cycles
- Weight: 41 g/m² ± 10%
- Roll Widths: 45" (114cm) ± 1"
- Master Roll Lengths: Average 50-100 Lm / 55-109 Lyd



PRODUCT APPLICATION EXAMPLES

- ⇒ RF Shielding
- ⇒ RF Windows
- ⇒ Medical Garments
- ⇒ Automotive
- ⇒ Aerospace

Accreditations:
RoHS: Compliant
Reach: Compliant
Acc. ISO 9001:2000

V Technical Textiles, Inc
4502 State Rt. 31
Palmyra, NY 14522
Phone: 315-597-1674
Fax: 315-597-6687
Web: www.vtechtextiles.com
Email: whoge@rochester.twcbc.com



Technical Textiles Inc.

A Woman's Owned Small Business

NWBOC®
WBE CERTIFIED

NWBOC®
EDWOSB CERTIFIED

Statex Productions &
Vertriebs GmbH
Kleiner Ort 11 28357
Bremen Germany
Tel: +49 421 275047/8,
Fax: +49 421 273643
info@statex.de