


1900102130KR



Shieldex® Conductive Nanking Fabric Tape Ultra Flex™


- Purpose: Conductive fabric tape for general use.
- Description: Nickel, Silver (Ni/Ag) woven fabric with adhesive.
- Surface Resistivity: < 0.3 Ω / □
- RF Shielding Effectiveness: Average 60dB from 30MHz to 10GHz.
- Abrasion Resistance: 500,000 Cycles
- Temperature Range: -30°C to 90°C / -22°F to 194°F
- Total Thickness: 0.005-0.006" (0.127mm to 0.150mm)
- Weight: 52 g/m² ± 10%
- Roll Slit Widths:
 - 1900102130KR13 = 1/2" (13mm)
 - 1900102130KR26 = 1" (26mm)
 - 1900102130KR50 = 2" (50mm)
 - 1900102130KR75 = 3" (75mm)



PRODUCT APPLICATION EXAMPLES

- ⇒ Base material for EMI/RFI gaskets
- ⇒ Base material for EMI/RFI garments
- ⇒ Passive static eliminator for copier, fax & printers
- ⇒ EMI/RFI cable shielding

Shielding Effectiveness IEEE 299



Accreditations:
 RoHS: Compliant
 Reach: Compliant
 Acc. ISO 9001:2015

Physical Address
 V Technical Textiles, Inc
 320 South Main Street
 Newark, NY 14513
 Phone: (315)-597-1674
 Fax: (315)-597-6687



Mailing Address
 V Technical Textiles, Inc
 4502 State Rt. 31
 Palmyra, NY 14522



www.vtechtextiles.com
 info@vtechtextiles.com



Statex Produktions -und Vertriebs GmbH
 Kleiner Ort 11 28357 Bremen Germany
 Tel: +49 421 27 50 47
 Fax: +49 421 27 36 43
 info@statex.de